



**Kömmerling®**

TODAY FOR TOMORROW



A FRESH BREEZE FOR YOUR HOME

**Kömmerling PremiDoor 88**

# EXPERIENCE A WHOLE NEW VISION

## Kömmerling PremiDoor 88

The lift/sliding door system Kömmerling PremiDoor 88 provides the basis for huge glazed areas, blurring the boundaries between inside and outside.

The system is very easy to operate: The floating doors are easy to open and close. And the classic design blends harmoniously into a wide variety of architectures.

The three sealing levels ensure excellent driving rain and sound insulation as well as outstanding windproof properties.

The large 88 mm installation depth not only ensures high stability, even with large glass surfaces, but also excellent thermal insulation values.

Kömmerling PremiDoor 88 is available in a wide range of surfaces: from PVC-U white to high-quality foiling in wood grain, plain and metallic shades to elegant aluminium shells in all available RAL colours, with anodised or powder coating.



### FLEXIBILITY



1 lift/sliding sash  
1 fixed pane



2 lift/sliding sashes  
1 fixed pane



1 lift/sliding sash  
2 fixed panes



2 lift/sliding sashes  
with floating mullion  
version  
2 fixed panes

- High profile stability for full-storey elements up to 2.90 m
- First-class heat transfer coefficient  $U_f = 1.2-1.3 \text{ W}/(\text{m}^2\text{K})$ ; Optionally, a  $U_D$  value of up to  $0.8 \text{ W}/(\text{m}^2\text{K})$  is possible
- Barrier-free transition from inside to outside
- Highly insulating WPC threshold (Wood Plastic Composite material)
- Safe function, high handling ease
- Optimal protection against driving rain, wind and sound
- Aluminium shells for an almost unlimited range of colours



#KömmerlingForTomorrow