



Kömmerling®

TODAY FOR TOMORROW



FOR ALL WHO BUILD ON THE FUTURE

Kömmerling 88 double seal Standard

FLOODED WITH LIGHT, QUIET AND PERFECTLY INSULATED

Kömmerling 88 double seal Standard

Even at first glance, Kömmerling 88 double seal scores points all around: with its generous glazed areas for rooms flooded with light, the minimalist-elegant design and the diverse design options. And at second glance, its innate values are compelling.

SUSTAINABLE

- High-insulation design with seven chambers in the sash and six in the frame
- Heat transfer coefficient with steels in the standard design: U_f value = 1.1 W/(m²K)
- Heat transfer coefficient with steels and additional insulation: U_f value = 1.0 W/(m²K)
- This results in a significant reduction in CO₂ emissions and high energy costs

USER-FRIENDLY

- Meets the highest sound insulation requirements
- Designed for burglar-resistant hardware
- Improved handling ease and reliable functionality through the use of state-of-the-art technology
- Easy to clean, long-lived and robust

ADAPTABLE

- Elegant design of straight lines
- Laminated in woodgrains, plain colours and metallic colours or classic PVC-U white

INNOVATIVE

- For windows with 88 mm installation depth up to resistance class RC 2 (MC 2)
- For ultra-modern triple glazing or functional glazing with a thickness of up to 58 mm
- Large glazed areas and narrow, extremely stable profiles



#KömmerlingForTomorrow