



You have decided for a modern, high-quality mattex/woodec foil. To ensure that you can enjoy it for a long time, please follow the instructions below:

- > A damp cotton or microfibre cloth is usually sufficient for removing normal soiling. In the case of heavier soiling in conjunction with soapy water.
- > Depending on the degree of soiling, the use of special cleaning agents may be necessary. Please observe our product recommendations and cleaning instructions, which are based on internal tests by the foil manufacturer.
- > Do not clean in direct sunlight.
- > Always test the cleaning agent on a non-visible area before cleaning.
- > Always use a cotton or microfibre cloth for cleaning and do not use abrasive cleaning agents.
- > Always move the cleaning agent along the profile.
- > Do not use dry cleaning agents, but always moisten with the recommended cleaning agents.
- > After cleaning, rinse the cleaning surface with plenty of warm water and then wipe completely dry.
- > Improper use of cleaning agents and cleaning aids can lead to the destruction of the film.

*) In each case in conjunction with Clean Primer 1101 or 1226

OTTOSEAL S 730*	Connection joint silicone for external RAL installation
OTTOSEAL S 120*	Premium glazing rebate silicone
OTTOSEAL M 360*	Hybrid sealant for building construction/connection joints
Triflex ProDetail	Prior cleaning with Triflex Cleaner

- > For masking work: PVC adhesive tape type HS 51013 from Honer Industrietechnik
- > We recommend plastering mouldings from the following manufacturers: Würth, Protector, 3ks
- > For sealing, the following products have been successfully tested for adhesion and compatibility:

Due to the mattness of the film, not all adhesives, sealants, etc. will adhere. We recommend the following products:



WE RECOMMEND THE FOLLOWING CLEANING AGENTS:

	Soapy water	Weiss Chemie CL 360.110	Weiss Chemie CL 360.170	Weiss Chemie CL 360.180	Weiss Chemie CL 300.150	Ika Chemie Planofix HB	Heinrich König Eco-cleaner	Fenoplast Fenosol S20	Soudal PU Building foam remover
Multi-purpose grease	x	x							
Precision mechanics oil	x	x							
Wood stain		x	x	x		x			
Lime mortar		x	x	x		x			
Plaster		x	x	x		x			
Cement mortar		x	x	x		x			
Wood impregnation								x	
Coating lime		x	x	x		x	x		
Emulsion paint					x				
Building foam									x
Acrylic paint					x			x	



Please be sure to follow the manufacturer's recommendations for use.

For soiling not mentioned here, please refer to the cleaning recommendations of the foil manufacturer. Click here for the latest table:

https://continental-ssl.mediavalet.com/portals/Reinigungsempfehlung_ExteriorFilms

